



7741 North 68th Avenue  
Glendale, Arizona 85303

## Galvalast™ Fence Warranty

Thank you for choosing U. S. Pool Fence Co. for your pool fencing needs. You have purchased our Galvalast™ hot dip galvanized fence. This fence will provide you will years of service with far less maintenance then our standard fence.

Please keep this letter with your important documents as it explains your warranty and required maintenance. As stated in your original contract, your fence has the following warranty:

U.S. Pool Fence Company warrants the structural integrity and workmanship of the original Purchaser for two (2) years, excluding damage caused by wind, water, ground movement, collision, or gate slamming. **Purchaser is responsible for proper maintenance, including, but not limited to, gate adjustments, bolt tightness, paint touch-up and the like.**

U.S Pool Fence warranties the Galvalast™ panels and posts for 50 years against rust through. This warranty covers only the Galvalast™ panels and posts manufactured and installed by U.S. Pool Fence Co., Inc. All other parts used in the fence, such as fasteners, latches, hinges, springs, etc are covered under their manufacture's warranty. All other aspects of the fence are covered by our standard two year workmanship warranty.

It is vital that any suspected warranty issues be reported to us immediately. Failure to report issues with your fence will make the issue more difficult and expensive to repair or replace. Your warranty claim may not be honored if damage to the fence is allowed to worsen due to failure of timely notification.

### Fence Maintenance

**Paint Touch Up:** While your fence is protected by our industry leading Galvalast™ undercoat, damage to your fence's powder coat finish can occur. This is normal wear and tear. For the best appearance and life of your fence's finish we recommend inspecting for knicks and scratches every 6 to 12 months.

Touch up knicks and scratches by using a fine grit sandpaper and sand down the nick or scratch until it is smooth. Only light sanding is needed. Do not sand into the Galvalast™ undercoat and never use an electric sander or grinder! Shake the touch up paint bottle well before using. Apply the touch up paint using the brush built into the cap. If you are in need of extra touch up paint, you may pick small touch-up bottles in our office at no charge. We also offer spray cans for an additional charge.

**Gate Maintenance:** Every 3-6 months apply a light coat of oil or lubricating spray to hinges. Do not slam your gate or prop it open at any time.

Proper maintenance is the customer's responsibility. Failure to follow these guidelines will void all warranties.